



## Instruction Manual for BD1100 & BD1150 Personal Vault



**Warning: For maximum security against theft and unwanted entry Bulldog Vaults BD1100 & BD1150 Personal vaults must be stored in the mounting bracket at all times.**

**First Time Use of the Safe:** The personal safe is supplied with two keys to unlock the safe from the mounting bracket and open it. To remove the safe from the mounting bracket insert the key into the lock and turn it all the way to the right to the unlock position. While holding the key in the unlock position, pull the safe from the mounting bracket. The key will automatically return to the locked position when released. To open the safe once removed from the mounting bracket turn the key all the way to the right to the unlock position and raise the top lid. To reinstall the safe into the mounting bracket turn the key all the way to the right to the unlock position. While holding the key in the unlock position insert the safe all the way into the bracket and release the key. If necessary turn the key to the left to ensure it is all the way in the lock position and remove the key. The safe is now secure in the mounting bracket.

**Mounting the Bracket:** First locate the six mounting screws and the six square spacers that were provided with your new safe. The mounting bracket has two different sides. The side with the six recessed 1" square indentions should be placed against the mounting surface. The opposite side has six ½" holes that will allow clearance for the screwdriver when installing the screws through the bracket, spacers and into the mounting surface. (Note: If the bracket is mounted directly to the mounting surface without using the spacers the safe must be placed into the bracket upside down to allow clearance for the lift handle.)

**Using Your Safe with the Included Security Cable:** One pre drilled slot has been provided on your new safe to allow the use of the security cable. To install the security cable, follow the instructions below.

1. First, loop one end of the security cable around a stationary object and back through the loop on the other end of the cable.
2. Then, insert the loose end of the security cable into the open safe allowing the cable to rest in the pre drilled slot while the metal cable stop in inside of the safe. Close the lid, lock the safe and remove the key. The safe will now be securely mounted the stationary object.

**For maximum security against theft and unwanted entry Bulldog Vaults BD1100 & BD1150 Personal vaults must be stored in the mounting bracket at all times.**

**Warranty:** Bulldog Vaults are protected by a full one year guarantee that entitles the owner to free repair or replacement of the vault if the product failure was cause by a defective part or faulty workmanship. This guarantee lasts for one year from the date of purchase. The repair or replacement will require the original purchase receipt. Any vault returned to Bulldog Vaults must be returned using a Return Authorization number and shipped at the owner's expense. This RA number may be obtained by calling the service department at 800.843.3483. Any items returned to Bulldog Vaults without the said RA number may be refused and returned to the sender at their expense. Once the vault is received it will be evaluated. If the vault is deemed to be defective it will be repaired or replaced at the discretion of Bulldog Vaults.